



**NOTES:**

1. GATE FRAMES SHALL BE CONSTRUCTED OF 51 O.D. GALVANIZED STEEL PIPE SHOP BENT, WELDED AND GROUND SMOOTH.
2. CHAIN LINK FENCE TO BE BLACK VINYL COATED .38 WOVEN MESH, 9 GAUGE. (11 GAUGE GALVANIZED STEEL CORE), FASTENED TO LINE POSTS, ALL RAILS, AND GATE FRAMES WITH 3.5 (9 GAUGE) KNUCKLED FASTENERS
3. FINISH TO BE BLACK GLOSS ENAMEL POLYESTER POWDER COATING. PRIOR TO POWDER COATING, ALL SURFACES TO BE TREATED WITH PARKER BONDERITE AND CHLOROETHYLENE OR APPROVED EQUALS. POWDER COATING MUST BE A POLYESTER 2000 SERIES, 5 MIL THICKNESS, APPLIED ELECTROSTATICALLY AND OVEN CURED TO A SMOOTH AND EVEN SURFACE.
4. PADLOCK RETENTION CLASP TO BE INSTALLED FOR GATE.
5. SEE SPECIFICATIONS FOR FENCE MATERIAL REQUIREMENTS.
6. NO PLASTIC FITTINGS ARE TO BE USED, INSTALL FENCE POSTS PRIOR TO PLACING ASPHALT PAVING AND COLOUR SURFACE SYSTEM.
7. GATE LOCATIONS INDICATED ON DRAWINGS SHALL BE CONFIRMED ON SITE BY THE CITY.
8. POST SIZE TO BE APPROVED BY CERTIFIED ENGINEER IF FENCE IS USED WITH WINDSCREEN.
9. ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.