

Planning and Development Services Building Division

8850 McLaughlin Road, Unit 1 Brampton, ON L6Y 5T1

Building Permit Requirements

New Industrial, Commercial or Institutional Projects or High-Rise Residential Buildings

Building Permit Application

The following is required at submission. Incomplete applications cannot be accepted.

1. COMPLETED APPLICATION FORMS.

- · Application for a Permit to Construct or Demolish
- Schedule 1: Designer Information
- · Applicable Law Checklist
- · General Review Commitment Certificate
- Detailed Letter of Use describing the nature of the operation or business, the number of employees and the occupant load.
 Industrial storage or manufacturing uses shall include a detailed description of the processes and materials or chemicals used or stored and the method of storage
- Completed Financial Contribution Form (provided by Building Division or available on the website www.brampton.ca)

2. PLANS AND SPECIFICATIONS

- · Legal Property Survey
- 2 sets of site plan approved drawings. Building Permit Applications will not be accepted without site plan approval
- 2 complete sets of drawings architectural, structural, HVAC, plumbing, electrical (sprinkler system complete with hydraulic calculations and fire alarm system, where applicable)
- 2 copies of BMEC authorization (where applicable)
- · 1 copy of HVAC calculations
- · 1 copy of soil engineer's report
- 2 sets of specifications (where applicable)
- 1 copy of Supplementary Standard SB-10 forms (where applicable)
- 1 copy of Proposal for Alternative Solution (where applicable)

3. BUILDING PERMIT FEE

- The building permit fee is based on the service index for the classification of the work proposed and the floor area in m²
 of the work involved
- (Fee = Service Index X Area)
- Refer to Building By-law 387-2006 as amended for Fee Schedule

Building Permit Issuance

The following items must be completed prior to issuance of a building permit:

- 1. Outstanding balance of permit fees is due and payable at the time of permit issuance. The applicant will be contacted upon completion of the plans review and advised of permit fees and any outstanding issues.
- 2. Provide proof of other statutory requirements (applicable law) where it applies in accordance with O.B.C. Div A, 1.4.1.3 for example:
 - Finance Department payment of development charges and parkland contribution
 - Conservation Authority permit from Toronto Region Conservation Authority or Credit Valley Conservation Authority
 - Ministry of Transportation land use or building permit
 - Proof of Filing of Record of Site Conditions
 - Proposal for Alternative Solution requires a deposit of \$419.31 at time of application plus \$113.36 per hour review time.
- 3. Where a permit is to be issued for construction within a common element of a registered condominium a Notice of Permission to Construct form, signed by an authorized agent of the condominium corporation, shall be submitted for the authorization of work to be undertaken within the common element of the building or property.
- Residential buildings intended for condominium registration must be registered with TARION and have an Ontario New Home Warranty program reference number.

Other Telephone Numbers

Credit Valley Conservation Authority 1-800-668-5557

Toronto and Region Conservation Authority (416) 661-6600

Permits Tel. 905-874-2401

Book Inspections www.brampton.ca/inspections

Zoning Services
ZoningInquiries@brampton.ca

Application for a Permit to Construct or Demolish This form is authorized under subsection 8(1.1) of the Building Code Act, 1992.

		For use b	y Principa	I Authority				
Application number:			Permit r	Permit number (if different):				
Date received:			Roll nur	nber:				
Application submitted to:	THE CORP (Name of municip							
A. Project information								
Building number, street nam	ne					Unit number	Lot/con.	
Municipality		Postal code	•	Plan number/	other des	cription		
Project value est. \$				Area of work	(m ²)			
B. Purpose of applicat	ion							
New construction	Addition existing	building		ation/repair		Demolition	Conditional Permit	
Proposed use of building		Cu	urrent use of	building				
Description of proposed wo								
C. Applicant	Applicant is: (Owner o	or (Authorized				
Last name		First name		Corporation of	or partners			
Street address						Unit number	Lot/con.	
Municipality		Postal code	Postal code			E-mail		
Telephone number Fax			Cell number					
D. Owner (if different f	rom applicant)							
Last name		First name		Corporation of	or partners	hip		
Street address						Unit number	Lot/con.	
Municipality		Postal code)	Province		E-mail	1	
Telephone number		Fax				Cell number		

E. Builder (optional)						
Last name	First name	Corporation or partnersh	nip (if applicable)			
Street address			Unit number	Lot/con.		
Municipality	Postal code Province E-mail					
Telephone number	Fax		Cell number			
F. Tarion Warranty Corporation (Ontario	New Home Warrant	y Program)				
i. Is proposed construction for a new home Plan Act? If no, go to section G.		<u> </u>	Ye	es No		
ii. Is registration required under the Ontario	o New Home Warranties	s Plan Act?	Ye	es No		
iii. If yes to (ii) provide registration number((s):					
G. Required Schedules						
i) Attach Schedule 1 for each individual who revi	iews and takes responsil	bility for design activities.				
ii) Attach Schedule 2 where application is to cons	struct on-site, install or re	epair a sewage system.				
H. Completeness and compliance with a	applicable law					
This application meets all the requirements of clauses 1.3.1.3 (5) (a) to (d) of Division C of the Building Code (the application is made in the correct form and by the owner or authorized agent, all applicable fields have been completed on the application and required schedules, and all required schedules are submitted). Payment has been made of all fees that are required, under the applicable by-law, resolution or						
is made.	regulation made under clause 7(1)(c) of the <i>Building Code Act, 1992</i> , to be paid when the application Yes No is made.					
) This application is accompanied by the plans and specifications prescribed by the applicable by-law, resolution or regulation made under clause 7(1)(b) of the <i>Building Code Act, 1992</i> .					
ii) This application is accompanied by the information and documents prescribed by the applicable by- law, resolution or regulation made under clause 7(1)(b) of the <i>Building Code Act, 1992</i> which enable the chief building official to determine whether the proposed building, construction or demolition will contravene any applicable law.						
y) The proposed building, construction or demolition will not contravene any applicable law. Yes No						
I. Declaration of applicant						
I (print name) 1. The information contained in this applicate documentation is true to the best of my limited.	knowledge.		cifications, and oth	clare that: er attached		
If the owner is a corporation or partnersh Date	Signature of applicant	o bind the corporation or p	oartnersnip. —			

Personal information contained in this form and schedules is collected under the authority of subsection 8(1.1) of the *Building Code Act, 1992*, and will be used in the administration and enforcement of the *Building Code Act, 1992*. Questions about the collection of personal information may be addressed to: a) the Chief Building Official of the municipality or upper-tier municipality to which this application is being made, or, b) the inspector having the powers and duties of a chief building official in relation to sewage systems or plumbing for an upper-tier municipality, board of health or conservation authority to whom this application is made, or, c) Director, Building and Development Branch, Ministry of Municipal Affairs and Housing 777 Bay St., 2nd Floor. Toronto, M5G 2E5 (416) 585-6666.

Schedule 1: Designer Information

Use one form for each individual who reviews and takes responsibility for design activities with respect to the project.

A. Project Information				
Building number, street name			Unit no.	Lot/con.
Municipality	Postal code	Plan number/ other descrip	tion	
B. Individual who reviews and takes	responsibili	ty for design activities		
Name		Firm		
Street address			Unit no.	Lot/con.
Municipality	Postal code	Province	E-mail	,
Telephone number	Fax number		Cell number	
C. Design activities undertaken by Division C]	ndividual ide	ntified in Section B. [Bu	ilding Code Tab	ole 3.5.2.1. of
House Small Buildings Large Buildings Complex Buildings Description of designer's work	Building Detecti	– House g Services on, Lighting and Power otection		
D. Declaration of Designer				
I		de	eclare that (choose	one as appropriate):
(print name) I review and take responsibility for the design work on behalf of a firm registered under subsection 3.2.4.of Division C, of the Building Code. I am qualified, and the firm is registered, in the appropriate classes/categories.				
Individual BCIN:				
Firm BCIN:				
I review and take responsibilit under subsection 3.2.5.of Divi		uilding Code.	opriate category as	an "other designer"
Basis for exemption from	registration:			
The design work is exempt from	-	-	ents of the Building	g Code.
I certify that: 1. The information contained in this schedule is true to the best of my knowledge. 2. I have submitted this application with the knowledge and consent of the firm.				
Date		Signature of Designer		

NOTE:

- 1. For the purposes of this form, "individual" means the "person" referred to in Clause 3.2.4.7(1) (c).of Division C, Article 3.2.5.1. of Division C, and all other persons who are exempt from qualification under Subsections 3.2.4. and 3.2.5. of Division C.
- 2. Schedule 1 is not required to be completed by a holder of a license, temporary license, or a certificate of practice, issued by the Ontario Association of Architects. Schedule 1 is also not required to be completed by a holder of a license to practise, a limited license to practise, or a certificate of authorization, issued by the Association of Professional Engineers of Ontario.

CITY OF BRAMPTON - BUILDING DIVISION

SECTION Gi. DOCUMENTS ESTABLISHING COMPLIANCE WITH APPLICABLE LAW (OBC Div. A - 1.4.1.3.)

Permit Application No.	Project Location		
	#	street	unit/suite

Explanation:

Applicable Law - Applicable law is other regulations for which approval must be obtained before a building permit can issue. A complete list of Acts and Regulations that are "Applicable Law" is set out in Article 1.4.1.3 of Division A of the Ontario Building Code.

Instructions:

The most common Acts and Regulations are listed below with the documentation that must be provided before a building permit can issue. Check those that apply to your permit application and complete the declaration. The customer service plans examiner will assist you with any questions you may have about the regulations listed. The documents noted <u>must</u> be provided before a building permit can issue.

Details and Contact Information

A list of agencies and contact information is available at the Building Division or on the City of Brampton website

APPLICABLE LAWS (Note: This list provides only the most common approvals)

Description	REQUIRED DOCUMENTS (Provide copy)	Required Yes/No	Received
(Site Plan Control)	Site plan approved drawings		
(Zoning By-law)	Final & binding amendment		
(Division of Land)	Registered Plan or Deed		
(Minor Variance)	Final Decision from City Clerk		
(Demolition of Residential Property)	Council Approval		
3, ss.34.40.1 & 40.2	Heritage Permit	•	
(2)	Ministry of Culture approval		
(Financial Contribution)	Confirmation of payment from City of Brampton Finance Department		
(Cash in Lieu of Parkland)	Confirmation of payment from City of Brampton Finance Department		
(Flood plain or fill regulated area)	Construction and Fill Permit		
(Daycare centre with more than 5 children)	Approval from Ministry of Children and Youth Services		
(Demolition of all or part of a school)	Approval from Ministry of Education		
(Industrial or commercial to agricultural, residential or park)	File Record of Site Condition (RSC) and/or provide Certification of Property use (CPU)		
(Construction within 45m of the road or within 395m of an intersection of Hwys, 410 or 407)	Building and Land Use Permit issued by MTO		
	(Site Plan Control) (Zoning By-law) (Division of Land) (Minor Variance) (Demolition of Residential Property) 3, ss.34.40.1 & 40.2 (2) (Financial Contribution) (Cash in Lieu of Parkland) (Flood plain or fill regulated area) (Daycare centre with more than 5 children) (Demolition of all or part of a school) (Industrial or commercial to agricultural, residential or park) (Construction within 45m of the road or within 395m of an intersection of	(Site Plan Control) (Site Plan Control) (Site Plan Control) (Zoning By-law) (Division of Land) (Minor Variance) (Demolition of Residential Property) (Demolition of Residential Property) (Council Approval Heritage Permit (Cash in Lieu of Parkland) (Flood plain or fill regulated area) (Daycare centre with more than 5 children) (Demolition of all or part of a school) (Industrial or commercial to agricultural, residential or park) (Construction within 45m of the road or within 395m of an intersection of	(Provide copy) (Site Plan Control) (Zoning By-law) (Division of Land) (Minor Variance) (Demolition of Residential Property) (Provide copy) Final & binding amendment Registered Plan or Deed (Minor Variance) Final Decision from City Clerk (Demolition of Residential Property) Council Approval Heritage Permit Ministry of Culture approval (Financial Contribution) Confirmation of payment from City of Brampton Finance Department (Cash in Lieu of Parkland) Confirmation of payment from City of Brampton Finance Department (Flood plain or fill regulated area) Construction and Fill Permit Approval from Ministry of Children and Youth Services (Demolition of all or part of a school) Approval from Ministry of Education File Record of Site Condition (RSC) and/or provide Certification of Property use (CPU) (Construction within 45m of the road or within 395m of an intersection of

APPLICANT'S DECLARATION		
I,(print name) knowledge, all of the "applicable law"		signated on the above noted chart are, to the best of my t must comply before a permit is issued.
	Date	Signature

FOR OFFICE USE ONLY



COMMITMENT TO PROVIDE GENERAL REVIEW

Pursuant to OBC DIVISION C - Part 1 Subsection 1.2.2.

PROJECT INFORMATIO	DN			
PROJECT DESCRIPTION				
PROJECT LOCATION	# Street		Unit/Suite	
PROPERTY OWNER	Name: Address: # Street e-mail address: If the Owner is a corporation provide Name: Address: # Street e-mail address:		ontact name and contact Unit/Suite City	
	OVIDE GENERAL REVIEW			
Consultant Name:				
Address:	# Street	Unit/suite	City	Postal Code
this document to p conformity with the standards of the Or 2. All general review Inspector at: <u>inspe</u>	chitect or professional engineer warrants that rovide general review of the construction of the e plans and other documents that form the bashtario Association of Architects (OAA) and/or Preports by the architect or professional engineenctions.scheduling@brampton.ca rovide general review for any reason during constructions.	e building referenced to determ is for the issuance of a building p rofessional Engineers of Ontario er will be forwarded promptly to	ine whether the construct permit, in accordance with (PEO); the attention of the appli	ion is in general n the performance cable
Professional Discipline	ARCHITECTURAL STRUCTURAL MECHANICAL- CIVIL ELECTRICAL		MECHANICAL PLUMB	
Signature: Print Name: FOR OFFICE USE ONLY PERMIT APPLICATION #			Date:	
Review By: <u>(Bldg)</u> (Plmbg) (HVAC)	BC	CIN#	Date:	

City of Brampton



1 Property Location

** New Building Form **

A SEPARATE FORM MUST BE FILLED IN FOR <u>EACH USE</u> IN A MIXED-USE BUILDING

Site Plan #

Municip	al Address:						
		# Street			Unit		
Legal D	escription:	Lot/Block	Plan		Reference Plan	Description	
Proper	ty Owner:	_					
Contac	: Applicant/Agent:	_					
	Address:	# Street	Uni	i+	Town/City		Postal Code
	Telephone:	# Sueet	Fax				r Ustai Code
Prop	erty Use	Specific Intended U	lse :				
1 1 9 1							
These def	ISE ONLY: initions are applicable to pplicable to you.	o how Development Charges are applied	I only and are contained within the De	velopme	ent Charges By-laws 2	18-2004 to 224-20	004; please check off the building use(s)
The follow section.	wing definition applie	s to By-laws 218-2004, 221-2004 and 2	23-2004:				
"Non-Indu				d or inte	nded to be used for ar	ny use other than	for residential use or for industrial use, or
building o by-law, of	r structure has an office fice excludes office or a	administrative uses located within a shop	r greater than 50 percent of the total pping centre or plaza, and excludes o	gross flo ffice or a	oor area of the building administrative uses wh	g or structure. For ere such uses are	the purposes of the Development Charge e accessory to an industrial use.
and the sa	ale of commodities to the		ccessory to an industrial use, but doe				aw goods, storage and includes office use ce or administrative purposes unless it is
							ral system serving the function thereof, an here such exterior storage constitutes an
	ations - Applicab completed by ap	ole to the City of Brampton, the	he Region of Peel and Sch	ool B	oard By-laws		Office Use - Checked by
	exterior or commo Where a building of the area of land floors in the buildir Also includes: a) Floor area of a and partitions. (Cit b) Below grade, of	or structure does not have any walls, directly beneath the roof of the building or structure. I mezzanine and air supported structure, Region and School Board By-laws only that floor area used for retail, cor	the total floor area shall be the suing or structure and the total areas ure and space occupied by interior).	im total s of the			
В.	purposes (Region Deductible Are	and School Board By-laws).				sq.m.	
Б.		. Any part of the building or structure equipment related to the operation building or structure, stairwells, elev	or maintenance of the			sq.m.	
	B-2	. Any part of the building or structure exclusively for the temporary parkin for the provision of loading spaces				sq.m.	
	B-3	. The area of any self contained struc facility approved by the Building Ma				sq.m.	
	B-4	Parts of the building below establish used for retail, commercial, office, in warehousing purposes.				sq.m.	
	B-5	. Parts of the building below grade us parking	sed for non-commercial			sq.m.	
	B-6	The portion of the building or structure religious organization which is used				sq.m.	
C.	Multiple Unit F	Residential Buildings (# of su	ites):			<= 750 sq.ft.	
						> 750 sq.ft.	
and cer		ments made herein are correct	Signature of Applicant:			Name (Pleas	se print):
						Date:	
<u> </u>							

ONTARIO BUILDING CODE SUPPLEMENTARY STANDARD SB-10 PROJECT INFORMATION

Project:	Location:
Building Permit Application No.:	Date:

Architectura Information		Mechanical Information	_	Electrical Do Information	_
Name		Name		Name	
Address		Address		Address	
City	Province	City	Province	City	Province
Signature	Date(YY/MM/DD)	Signature	Date(YY/MM/DD)	Signature	Date(YY/MM/DD)

^{*}IF MORE DESIGNERS ARE INVOLVED, PROVIDE ADDITIONAL COPIES OF THIS FORM.

THIS CHECKLIST IS A CONVENIENCE DOCUMENT ONLY AND IS BASED ON THE ENERGY EFFICIENCY REQUIREMENTS DESCRIBED IN THE ONTARIO BUILDING CODE SUPPLEMENTARY STANDARD SB-10 DIVISION 3. THIS CHECKLIST IS NOT A SUBSTITUTE FOR COMPLYING WITH THE REQUIREMENTS OF THE ONTARIO BUILDING CODE. WHILE CARE HAS BEEN TAKEN TO ENSURE ACCURACY OF THIS CHECKLIST, DESIGNERS AND BUILDING OFFICIALS MUST REFER TO THE ACTUAL WORDING AND REQUIREMENTS OF THE ONTARIO BUILDING CODE (O.REG. 350/06 AND AMENDMENTS UP TO AMENDING O.REG. 315/12).

THIS CHECKLIST IS MADE AVAILABLE FOR CODE USERS BY THE MINISTRY OF MUNICIPAL AFFAIRS AND HOUSING. USERS SHOULD ALWAYS CONSULT WITH THE AUTHORITY HAVING JURISDICTION, IF THE CHECKLIST IS GOING TO BE SUBMITTED TO THAT AUTHORITY. THE MINISTRY OF MUNICIPAL AFFAIRS AND HOUSING DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR OVERSIGHTS RESULTING FROM THE INFORMATION CONTAINED HEREIN.

PLEASE FILL IN THE ACTUAL VALUES INSTALLED AND CHECK BOXES AS THEY APPLY.

OBC SB-10 COMPLIANCE SUMMARY

Energy Efficiency Design:

There are three energy compliance options to meet the requirements of OBC SB-10 Division 3. Please select the compliance option selected for this project. The energy efficiency of all buildings must be designed to:

Compliance Path		Forms to Complete
(A) Achieve the energy efficiency levels attained by conforming to the ASHRAE 90.1-2013, "Energy Standard for Buildings Except Low-Rise Residential Buildings" and Chapter 2 of SB-10 (Division 3). This compliance path includes both prescriptive and performance path options. Please proceed to Form A.	□ YES	FORM A
(B) Achieve the energy efficiency levels attained by conforming to the National Energy Code of Canada for Buildings 2015 and Chapter 3 of SB-10 (Division 3). This compliance path includes both prescriptive and performance path options. Please proceed to Form B.	□ YES	NECB
(C) Section 7 "Energy Efficiency" of 2014 ANSI/ASHRAE/USGBC/IES 189.1, excluding Sections 7.2.b, 7.4.7.3, 7.4.8 and 7.5	□ YES	

ONTARIO BUILDING CODE SUPPLEMENTARY STANDARD SB-10 PROJECT INFORMATION – ADDITIONAL DESIGNER SIGNATURES

Project:	Location:
Building Permit Application No.:	Date:

Designer Information (Other)*:	Designer In	formation (Other)*:	Designer In	formation (Other)*:
Specialty	Specialty		Specialty	
Name	Name		Name	
Address	Address		Address	
City Province	City	Province	City	Province
	_			
Signature Date(YY/MM/DD)	Signature	Date(YY/MM/DD)	Signature	Date(YY/MM/DD)

^{*}AS APPLICABLE TO SB-10 2017 PROVISIONS AND REQUIREMENTS.

THIS CHECKLIST IS A CONVENIENCE DOCUMENT ONLY AND IS BASED ON THE ENERGY EFFICIENCY REQUIREMENTS DESCRIBED IN THE ONTARIO BUILDING CODE SUPPLEMENTARY STANDARD SB-10 DIVISION 3. THIS CHECKLIST IS NOT A SUBSTITUTE FOR COMPLYING WITH THE REQUIREMENTS OF THE ONTARIO BUILDING CODE. WHILE CARE HAS BEEN TAKEN TO ENSURE ACCURACY OF THIS CHECKLIST, DESIGNERS AND BUILDING OFFICIALS MUST REFER TO THE ACTUAL WORDING AND REQUIREMENTS OF THE ONTARIO BUILDING CODE (O.REG. 332/12 AND AMENDMENTS UP TO AMENDING O.REG. 194/14 AND MINISTER RULING M-16-S-27.).

THIS CHECKLIST IS MADE AVAILABLE FOR CODE USERS BY THE MINISTRY OF MUNICIPAL AFFAIRS AND HOUSING. USERS SHOULD ALWAYS CONSULT WITH THE AUTHORITY HAVING JURISDICTION, IF THE CHECKLIST IS GOING TO BE SUBMITTED TO THAT AUTHORITY. THE MINISTRY OF MUNICIPAL AFFAIRS AND HOUSING DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR OVERSIGHTS RESULTING FROM THE INFORMATION CONTAINED HEREIN.

OBC SB-10 AND ASHRAE 90.1 - 2013 - COMPLIANCE SUMMARY

Form A

Project:	Location of Project:
Building Permit Application No.:	Climatic Zone (SB-10 Division 3 Section 1.3):

ASHRAE 90.1 – 2013 COMPLIANCE AS MODIFIED BY OBC SB-10 DIVISION 3					
The building design complies with the mandatory provisions of the following sections regardless of the compliance path:					
ASHRAE 90.1-2013 Standard Section	Compliance Column	Form			
5.4 BUILDING ENVELOPE AND SB-10 DIVISION 3	□ YES	FORM 5.4			
6.4 HEATING, VENTILATING AND AIR CONDITIONING	□ YES	FORM 6.3 or FORM 6.4			
7.4 SERVICE WATER HEATING SYSTEMS AND EQUIPMENT	□ YES	FORM 7.4			
8.4 POWER	□ YES	FORM 8.4			
9.4 LIGHTING	□ YES	FORM 9.4			
10.4 OTHER EQUIPMENT AND SB-10 DIVISION 3	□ YES	FORM 10.4			

METHOD OF COMPLIANCE						
Building Design must comply with either the Prescriptive Requirements or the Energy Cost Budget Method. Indicate which method was selected.						
Compliance Method	Compliance Column	Form				
PRESCRIPTIVE COMPLIANCE	□ YES	COMPLETE SECTION A-1				
ENERGY COST BUDGET METHOD	□ YES	COMPLETE SECTION A-2				

A-1: PRESCRIPTIVE COMPLIANCE – ASHRAE 90.1-2013 AND OBC SB-10						
The building design complies with the Prescriptive Compliance requirements of the following sections:						
Standard Section Reference		Compliance Column	Form			
Sec 5 BUILDING ENVELOPE	Prescriptive Requirements (5.5 of 90.1) Building Envelope Trade-Off (5.6 of 90.1)	□ YES □ YES	FORM 5.5 or FORM 5.6			
Sec 6 HVAC SYSTEMS	Simplified Approach for HVAC Systems Mandatory + Prescriptive Path Option	□ YES □ YES	FORM 6.3 or FORM 6.4			
Sec 7 SERVICE WATER HEATING	Prescriptive Path Option	□ YES	FORM 7.4			
Sec 9 LIGHTING	Prescriptive Requirements	□ YES	FORM 9.5			

A-2: ENERGY COST BUDGET METHOD – ASHRAE 90.1-2013 AND OBC SB-10				
	Compliance Column	Form		
The building design complies with the provisions of Section 11 of ASHRAE 90.1-2013, based on Division 3 of SB-10.	□ YES	FORM 11		

ASHRAE 90.1-2013 AND OBC SB-10 DIVISION 3— MANDATORY PROVISIONS Form 5.4

SECTION 5.4 MANDATORY PROVISIONS	
Building insulation has been designed to comply with section 5.4.1 of ASHRAE 90.1-2013 as modified by Chapter 2 of OBC SB-10.	□ YES
Building fenestration and doors have been designed to comply with section 5.4.2 of ASHRAE 90.1-2013 as modified by Chapter 2 of OBC SB-10.	□ YES
Building air leakage has been designed to comply with section 5.4.3 of ASHRAE 90.1-2013 as modified by Chapter 2 of OBC SB-10.	□ YES

Section 5.5 Overall Building Design Requirements					
The building design must comply with the following general requirements. If any of these requirements are not met, the prescriptive path cannot be pursued. Consider the building envelope trade-off compliance or the Energy Cost Budget Method Described in Chapter 11 of ASHRAE 90.1-2013:					
Gross Wall Area: m²					
Vertical Fenestration Area: m²	□ YES				
Vertical fenestration area is less than 40% of the gross wall area					
Gross Roof Area: m²					
Skylight Area: m²	□ YES				
Total skylight area does not exceed 3% of the gross roof area					
Where the main entrance is located on the south orientation and the south-oriented wall area					
is larger than west-oriented wall area, and where the south-oriented wall area is larger than					
east-oriented wall area, per ASHRAE 90.1-2013 5.5.4.5, either:					
(a) total east and west vertical fenestration areas are each less than 25% of total vertical	□ YES □ N/A				
fenestration area for the whole building, or	V50				
(b) east and west area-weighted SHGC is less than area-weighted SHGC for total	□ YES □ N/A				
fenestration					
Exception (from ASHRAE 90.1-2013 Section 5.5.4.5):					
Where electric space heating provides more than 10 per cent of the heating capacity, the	□ YES □ N/A				
building envelope shall comply with the requirements of Table SB 5.5-7 of SB-10, regardless of					
its climatic location					
For Climate Zone 5, minimum skylight fenestration area conforms to the requirements of PYES DYA					
ASHRAE 90.1-2013 5.5.4.2.3.					
Identify SB-10 Table used for maximum U-Factors or minimum RSI-Values :					

Complete the table on Form 5.5-2 to show compliance for all envelope components. Attach as many copies of this form as required to ensure that all envelope components are represented.

For all opaque surfaces, compliance must be demonstrated by meeting either:

- 1. The minimum R-values of insulation added in framing cavities and continuous insulation as specified in Tables SB5.5-5 to SB5.5-7.
- 2. The maximum U-factor, C-factor, or F-factor for the entire assembly as specified in Tables SB5.5-5 to SB5.5-7. U-factor is to be determined from tables in Appendix A of ASHRAE 90.1-2013 or through calculation methods described in ASHRAE 90.1-2013 Appendix Section A9.

For all fenestration products, compliance with U-factors, SHGC and VT must be determined for the overall fenestration product.

- 1. Fenestration shall have a U-factor and SHGC not greater than those specified in SB-10 Tables SB5.5-5 to SB5.5-7.
- 2. Where automatic daylighting controls are required in accordance with Section 9.4.1.1(e) or (f), fenestration shall have a ratio of VT divided by SHGC not less than that specified in Tables SB5.5-5 through SB5.5-7 for the appropriate fenestration area.
- 3. U-factor to be determined through CSA or NFRC rating or by using ASHRAE 90.1-2013 Appendix A default values.

Please complete the following table to include information on all walls, roofs, doors, and floors used in the design.

OPAQUE BUILDING ENVELOPE COMPONENTS							
Opaque Element - Description ⁽¹⁾	Space Conditioning Category ⁽²⁾	Class of Construction (3)	Criteria Max. U- Value ⁽⁴⁾ or Min RSI	Design U-Value ⁽⁴⁾ or RSI	Area Weighted Avg. Used ⁽⁵⁾ ?		
	□ NR □ R □ SH				□Y□N		
	□ NR □ R □ SH				□ Y □ N		
	□ NR □ R □ SH				□Y□N		
	□ NR □ R □ SH				□Y□N		
	□ NR □ R □ SH				□Y□N		
	□ NR □ R □ SH				□Y□N		
	□ NR □ R □ SH				□Y□N		
	□ NR □ R □ SH				□Y□N		
	□ NR □ R □ SH				□Y□N		
	□NR □R □SH				□Y□N		

Please complete the following table to include information on all fenestration products used in the design.

FENESTRATION ENVELOPE COMPONENTS									
Fenestration -	Space	Class of Construction	U-Va	lue ⁽⁴⁾	SHO	GC ⁽⁶⁾	VT/S	HGC	Area Weighted
Description ⁽¹⁾	Conditioning Category ⁽²⁾	(3)	Crit.	Des.	Crit.	Des.	Crit.	Des.	Average Used ⁽⁵⁾ ?
	□ NR □ R □ SH								□Y□N
	□ NR □ R □ SH								□Y□N
	□ NR □ R □ SH								□Y□N
	□ NR □ R □ SH								□Y□N
	□ NR □ R □ SH								□Y□N
	□ NR □ R □ SH								□Y□N
	□ NR □ R □ SH								□Y□N
	□ NR □ R □ SH								□Y□N
	□ NR □ R □ SH								□Y□N

- (1) Indicate if Element is a Wall, Roof, Floor, Door, Window or Skylight and a Tag or Description (eg Wall W1).
- (2) Select from Non-residential (NR), Residential (R), or Semiheated (SH).
- (3) Select from the subclasses of roofs, walls, floors, doors and fenestration provided in Tables SB5.5-5 to SB5.5-7 (eg. Steel Framed for walls). Note that curtain wall systems are considered a steel framed wall.
- (4) F-Factors can be used for floors and C-Factors for below Grade Walls as applicable.
- (5) Elements of the same type, space category, and class of construction can be averaged using area weighting to show compliance only if U-Values are used.
- (6) Design SHGC may be higher than the criteria if one of the exceptions from ASHRAE 90.1-2013 5.5.4.4.1 or 5.5.4.4.2 is applicable. Please use the space below to identify the fenestration elements (if any) which an exception for SHGC is being claimed.
- (7) Design VT/SHGC ratio may be lower than the criteria if one of the exceptions from ASHRAE 90.1-2013 5.5.4.6 is applicable. Please use the space below to identify the fenestration elements (if any) which an exception for VT/SHGC is being claimed.

SHGC and VT/SHGC EX	CEPTIONS
Fenestration Element	SHGC or VT/SHGC exception from ASHRAE 90.1-2013 5.5.4.4.1, 5.5.4.4.2, or 5.5.4.6

ASHRAE 90.1-2013 & SB-10 – SECTION 5.5 –BUILDING ENVELOPE TRADE-OFF OPTION

Form 5.6

Note that this option may only be pursued using the procedure described in ASHRAE 90.1-2013 Section 5.6 as modified by the requirements of Chapter 2 of SB-10

Calculated EPF for proposed building*: Calculated EPF for budget building*:	
Envelope performance factor (EPF) for proposed building is less than or equal to the envelope performance factor of the budget building.	□ YES
All components of the building envelope shown on architectural drawings or installed in existing buildings have been separately described and modeled in the proposed building design, with exception for envelope assemblies that cover less than 5% of the total area of its corresponding assembly type, and whose area can be included with another similar assembly (based on thermal properties and orientation) as noted in Section 5.6.1.1.	□ YES
A software program* incorporating the requirements of ASHRAE 90.1-2013 as modified by SB-10 has been used to calculate the EPF. A report from this software is attached.	□ YES
Name of software:	

^{*}Note that the EPF must be calculated by a simulation program which includes the requirements of ASHRAE 90.1-2013 as modified by SB-10.

If simplified HVAC method is used complete this form, otherwise proceed to Form 6.4.

	- 6	3
Number of Stories:	Gross floor area:	m²

Reference		Standard Compliance
6.3.1	The building is 2 stories or less in height and has a gross floor area less than 2,300 m ² .	□ YES
6.3.2	All of the requirements in Section 6.3 as outlined below must be met by each HVAC system in the facility.	
6.3.2.a	System serves a single HVAC zone.	□ YES
6.3.2.b	The equipment meets the variable flow requirements of Section 6.5.3.2.1.	□ YES □ N/A
6.3.2.c	If a cooling is installed, it is provided by a unitary packaged or split-system air conditioner that is either air-cooled or evaporatively cooled and meets the efficiency requirements shown in Tables 6.8.1-1, 6.8.1-2, and 6.8.1-4.	□ YES □ N/A
6.3.2.d	The system has an air economizer with outside airflow capacity and controls as required per Section 6.5.1., unless exempt.	□ YES □ N/A
6.3.2.e	Heating is provided by a unitary packaged or split-system heat pump, a fuel-fired furnace, an electric resistance heater or a baseboard system connected to a boiler. All heating equipment meets the efficiency requirements shown in Table 6.8.1-2, 6.8.1-4, 6.8.1-5, and 6.8.1-6 as modified by SB-10 Table SB 6.8.1-2017.	□ YES □ N/A
6.3.2.f	System meets the exhaust air energy recovery requirements of Section 6.5.6.1 as modified by SB-10, unless exempt.	□ YES □ N/A
6.3.2.g	The system is controlled by a manual changeover or dual setpoint thermostat.	□ YES
6.3.2.h	Heat pumps equipped with auxiliary internal electric resistance heaters (if any) have controls to prevent supplemental heater operation when the heating load can be met by the heat pump alone, unless exempt.	□ YES □ N/A
6.3.2.i	The system controls do not permit reheat or any other form of simultaneous heating and cooling for humidity control.	□ YES □ N/A
6.3.2.j	Systems are provided with a time switch that (1) can start and stop the system under different schedules for seven different day-types per week; (2) is capable of retaining programming and time setting during a loss of power for a period of at least 10 h; (3) includes an accessible manual override that allows temporary operation of the system for up to 2 h; (4) is capable of temperature setback down to 13° C during off hours; and (5) is capable of temperature setup to 32° C during off hours unless exempt.	□ YES □ N/A
6.3.2.k	Piping is insulated in accordance with values given in Table 6.8.3A and 6.8.3B. Insulation exposed to weather is suitable for outdoor service (i.e. protected by aluminum, sheet metal, etc. or painted with a coating that is water retardant and provides shielding from solar radiation).	□ YES □ N/A
6.3.2.I	Ductwork and plenums are insulated in accordance with Tables 6.8.2A and 6.8.2B and sealed in accordance with Section 6.4.4.2.1.	□ YES □ N/A
6.3.2.m	Specifications call for ducted air systems to be balanced.	□ YES □ N/A
6.3.2.n	Outdoor air intake and exhaust systems meet the controls requirements of Section 6.4.3.4.	□ YES □ N/A
6.3.2.0	Where separate heating and cooling equipment serve the same temperature zone, thermostats are interlocked to prevent simultaneous heating and cooling.	□ YES □ N/A
6.3.2.p	Systems with a design supply air capacity greater than 5,000 L/s have optimum start controls.	□ YES □ N/A
6.3.2.q	In spaces larger than $50m^2$ and with design occupancy ≥ 25 people per $100m^2$, the system complies with the demand control ventilation requirements in Section 6.4.3.8, unless exempt.	□ YES □ N/A
6.3.2.r	The system complies with the door switch requirements of Section 6.5.10.	□ YES □ N/A

Reference		Standard Compliance	
	Mandatory Provisions – Complete only if simplified HVAC method is not used.		
6.4.1	Equipment shown in 6.8.1-1 through 6.8.1-13 meets the minimum performance (as modified by SB-10 Table SB 6.8.1-2017) at the specified rating conditions in accordance with the test procedures in the tables or those in SB-10 Section 6.4.1.A.	□ YES	
6.4.2.1	Load calculations for heating and cooling systems are done as per ASHRAE Standard 183-2007 for selection of all equipment and systems.	□ YES	
6.4.2.2	Pressure drop through each device and pipe segment in the critical circuit at design conditions has been calculated in accordance with generally accepted engineering standards and handbooks.	□ YES	
6.4.3	Mandatory controls requirements are met by all the equipment in the building as outlined in Section 6.4.3.	□ YES	
6.4.4.1	Ductwork, piping, and equipment insulation meets the requirements of Section 6.4.4.1.	□ YES	
6.4.4.2	Construction documents specify sealing and pressure testing of ductworks and plenums as per Section 6.4.4.2.	□ YES	
6.4.5	Site-assembled or site-constructed walk-in coolers and freezers shall conform to the requirements of Section 6.4.5.	□ YES	
6.4.6	All refrigerated display cases shall conform to the requirements of Section 6.4.6., including Section 6.4.1.1 and Tables 6.8.1-1 through 6.8.1-13 as modified by SB-10.	□ YES	
	Prescriptive Requirements – Complete this section if not using Energy Cost Budget Method.		
6.5.1	Each cooling system that has a fan employs either airside or waterside economizer unless exempt.	□ YES □ N/A	
6.5.1.1	Airside economizers are capable of modulating outdoor air dampers to provide up to 100% design airflow for cooling and the system provides relief capacity for such airflow.	□ YES □ N/A	
6.5.1.2.1	Waterside economizers are capable of cooling supply air up to 100% of the expected system cooling load at the conditions listed under Section 6.5.1.2.1, unless exempt.	□ YES □ N/A	
6.5.1.2.2	Waterside economizer systems with pressure drop greater than 45kPa are isolated from main cooling loop to reduce pumping input in the normal cooling mode.	□ YES □ N/A	
6.5.1.3	Economizer systems incorporate integrated economizer controls per ASHRAE 90.1-2013 6.5.1.3	□ YES □ N/A	
6.5.1.4	Economizer operation does not increase the building heating energy use during normal operation, except as allowed under ASHRAE 90.1-2013 6.5.1.4	□ YES □ N/A	
6.5.1.5	Systems with hydronic cooling and humidification systems designed to maintain inside humidity at a dew-point temperature greater than 2°C use a water economizer if required by ASHRAE 90.1-2013 6.5.1.	□YES □N/A	
6.5.2	Simultaneous heating and cooling is limited with compliant zone, hydronic system, dehumidification, and humidification controls as per Section 6.5.2.	□ YES □ N/A	
6.5.3	Cooling system fan controls comply with the requirements of 6.5.3.2 and 6.5.3.3.	□ YES □ N/A	
6.5.3.1	Fan systems exceeding 4kW nameplate power have fan power limitations 10% below limitations specified in ASHRAE 90.1-2013 Table 6.5.3.1.1-1 and Section 6.5.3.1.2.	□ YES □ N/A	
6.5.4.1	Boiler systems with design input of \geq 293 kW comply with the turndown ratio specified in Table 6.5.4.1.	□ YES □ N/A	
6.5.4.2	Pumping systems greater than 7.5 kW employ compliant variable flow controls, unless exempt		
6.5.4.3	Chilled water plants with more than one chiller and boiler plants with more than one boiler reduce loop water flow automatically whenever a chiller or boiler is shut down and isolated.	□ YES □ N/A	
6.5.4.4	Hydronic systems exceeding design capacity of 88 kW include controls to reset supply water temperature based on building loads or outdoor air temperature, unless exempt.	□ YES □ N/A	
6.5.4.5	Hydronic heat pumps and unitary air-conditioners include automatic water shutoff when the compressor is off (unless units are employing water economizer) and those having total pump system power greater than 3.7 kW have variable speed control.	□ YES □ N/A	
6.5.4.6	Chilled water and condenser water pipe is sized according to Table 6.5.4.6.	□ YES □ N/A	
6.5.5	Open-circuit cooling towers have fans meeting the energy efficiency requirements of Section 6.5.5.3 and have flow turndown in compliance with 6.5.5.4.	□ YES □ N/A	

SECTION	6 HVAC – 6.4 MANDATORY PROVISIONS AND 6.5 PRESCRIPTIVE REQUIREN	MENTS Form 6.4
6.5.5.2	All heat rejection equipment provide fan controls that comply with Section 6.5.5.2, with variable speed drives on fan motors \geq 5.6 kW.	□ YES □ N/A
6.5.6.1	Exhaust air energy recovery is provided for fan systems meeting the conditions listed on Table 6.5.6.1. Energy recovery is at least 55% effective and bypass is available to permit air economizer operation as per Section 6.5.1.1.	□ YES □ N/A
6.5.6.2	Condenser heat recovery system for heating or preheating hot water is provided, unless exempt.	□ YES □ N/A
6.5.7.1	Kitchen exhaust systems are designed as per Section 6.5.7.1.	□ YES □ N/A
6.5.7.1.5	Specifications call for performance testing of kitchen exhaust systems.	□ YES □ N/A
6.5.7.2	Laboratory fume hoods with a total exhaust system flow > 2,360 L/S comply with the variable air volume control requirements of 6.5.7.2.	□ YES □ N/A
6.5.8.1	Heating of unenclosed spaces is done by radiant heating, except loading docks with air curtains.	□ YES □ N/A
6.5.9	Cooling equipment with hot-gas bypass controls is designed with multiple steps of unloading or continuous capacity modulation, with capacity limits as indicated in Table 6.5.9 for VAV systems. Constant volume units do not have hot gas bypass.	□ YES □ N/A
6.5.10	All conditioned spaces with a door to the exterior have door switches interlocked with heating and cooling controls per Section 6.5.10, unless exempt.	□ YES □ N/A
6.5.11	Refrigeration systems that are comprised of refrigerated display cases, walk-in coolers, or walk-in freezers connected to remote compressors, remote condensers, or remote condensing units meet the requirements of Sections 6.5.11.1 through 6.5.11.2.	□ YES □ N/A

Reference	Item	Standard Compliance
7.4.1	Load calculations for heating and cooling systems are done in accordance with manufacturer's published sizing guidelines or generally accepted engineering standards and handbooks for selection of all equipment and systems.	□ YES
7.4.2	All equipment used solely for the following purposes meets or exceeds the efficiency requirements and testing criteria of Table 7.8, as modified by SB-10 7.4.2.A, unless exempt.: • heating potable water • pool heaters • hot water storage tanks Exemptions:	□ YES □ N/A
7.4.3	 The following service hot water piping is insulated to levels shown in Table 6.8.3-1: a. Recirculating system piping, including piping of a circulating tank type water heater. b. The first 2.4m of outlet piping for a constant temperature non-recirculating storage system. c. Inlet pipe between storage tank and heat trap in a non-recirculating storage system. d. Pipes that are externally heated (e.g. heat tracing). 	□ YES □ N/A
7.4.4.1	All water-heating systems have temperature controls that are adjustable down to 49°C or lower. • Exception: Equipment that must be protected from corrosion, as per manufacturer's installation instructions.	□ YES □ N/A
7.4.4.2	Systems designed with pipe heating systems such as heat trace have temperature or time controls to disable during extended periods without hot water demand.	□ YES □ N/A
7.4.4.3	Public lavatories have outlet temperature controls that limit the discharge temperature to 43°C.	□ YES □ N/A
7.4.4.4	Tanks with remote heaters have circulation pump controls to limit operation of circulation pumps to a maximum of five minutes after the end of the heating cycle.	□ YES □ N/A
7.4.5.1	Pool heaters have readily accessible ON/OFF switch without adjusting the thermostat setting. Gas-fired heaters do not have standing pilot lights.	□ YES □ N/A
7.4.5.2	Per SB-10 7.4.5.2, heated exterior public pools and public spas shall be equipped with pool covers, unless over 60% of their energy for heating (computed over an annual operating season) is derived from site-recovered or site-solar energy.	□ YES □ N/A
7.4.5.3	Pool heaters and circulation pumps have time switches, unless exempt.	□ YES □ N/A
7.4.6	Heat traps are provided to all vertical risers serving storage water heaters and storage tanks.	□ YES □ N/A
	Prescriptive Requirement – Complete this section if not using Energy Cost Budget Method.	
7.5	Boiler systems that provide space heating as well as service water heating meet the conditions of Sections 7.5.1 and 7.5.2.	□ YES □ N/A
7.5.3	Gas service hot-water systems with a total installed gas water-heating input capacity of 293 kW or greater, shall have a minimum input capacity-weighted average thermal efficiency of 90%, unless exempt.	□ YES □ N/A

ASHRAE 90.1 & SB-10- SECTION 8,9 &10 POWER, LIGHTING AND OTHER EQUIPMENT

SECTION	8 POWER – 8.4 MANDATORY PROVISIONS	Form 8.4
Reference	Item	Standard Compliance
8.4.1	Feeder conductors and branch conductors are sized as per Section 8.4.1.	□ YES
8.4.2	At least 50% of all 125 volt 15- and 20-Ampere receptacles (installed in conference rooms, rooms used primarily for printing and/or copying functions, breakrooms, classrooms, and individual workstations), and at least 25% of branch circuit feeders (installed for modular furniture not shown on the construction documents), are provided with automatic receptacle controls that function on a) time-of-day schedule or b) occupant sensor or c) occupancy signal from another control or alarm system, with exceptions as listed, as modified by SB-10.	□ YES □ N/A
8.4.3	Unless exempted, measurement devices are shown in design documents to monitor the total electrical energy, as well as the electrical energy use separately for HVAC systems, interior lighting, exterior lighting, and receptacle circuits. For buildings with tenants, these systems are separately monitored for the total building and (excluding shared systems) for each individual tenant. Data recording and storage capabilities meet the requirements of 8.4.3.2.	□ YES □ N/A
8.4.4	Low Voltage Dry-Type Distribution Transformers meet nominal efficiencies shown in Table 8.4.4, unless exempt.	□ YES □ N/A

SECTION S	LIGHTING- MANDATORY PROVISIONS CHECKLIST	Detailed Form 9.4-1
Reference	Item	Standard Compliance
9.4.1.1	For each space in the building, all of the lighting control functions indicated in ASHRAE 90.1-2013 Table 9.6.1, for the appropriate space type in column A, have been implemented, as described by Section 9.4.1.1: a. Local Control b. Restricted to manual ON c. Restricted to partial automatic ON	□ YES
31.12.12	 d. Bilevel lighting control e. Automatic daylight responsive controls for sidelighting f. Automatic daylight responsive controls for toplighting g. Automatic partial OFF (full OFF complies) h. Automatic full OFF i. Scheduled shutoff 	
9.4.1.2	Lighting for parking garages is controlled by automatic shutoff controls meeting the	□ YES □ N/A
	requirements outlined in Section 9.4.1.2. Lighting for parking garages is controlled by one or more devices that reduce lighting power of each luminaire by at least 30% when there is no activity within a zone for at most 30 minutes. Each lighting zone for this requirement cannot exceed 334 m², except daylight transition zones and ramps without parking. Daylight transition zones in parking garages are controlled separately. These are automatically controlled to reduce by at least 50% from sunset to sunrise. Parking garage luminaires within 6m of perimeter walls that have a net opening-to-wall ratio of at least 40% automatically reduce power in response to daylight, except daylight transition zones	□ YES □ N/A □ YES □ N/A
	and ramps without parking.	·
9.4.1.3	Additional control is provided to the special applications listed in Section 9.4.1.3	□ YES □ N/A
9.4.1.4	Exterior lights are shut off by an automatic photosensor when available daylight is sufficient, unless exempt.	□ YES □ N/A
	All building façade and landscape lighting is automatically shut off overnight as per 9.4.1.4.	□ YES
	Exterior lighting not for façade or landscape, including for signage, is automatically controlled to reduce lighting power by at least 30% overnight or during inactive periods as per 9.4.1.4. (Uncovered parking areas are exempt per SB-10)	□ YES
9.4.2	Exterior building lighting power complies with ASHRAE 90.1-2013 9.4.2 as modified by SB-10. Form 9.4.2 may be used to demonstrate compliance.	□ YES
9.4.3	Third party functional testing of all lighting control devices and systems is specified in the construction documents.	□ YES

SECTION	SECTION 9.4 LIGHTING – EXTERIOR LIGHTING POWER MANDATORY COMPLIANCE	
Reference		Standard Compliance
9.4.3	Exterior Lighting Zone (Table SB 9.4.2-2–2017)	
	Total Installed Exterior Lighting Power W ≤ value of exterior LPA W *	□ YES □ N/A
	List any exemptions that apply:	

^{*} Calculation worksheet (FORM 9.4-3) is required.

SECTION	9.5 LIGHTING – INSTALLED LIGHTING POWER PRESCRIPTIVE COMPLIANCE	Form 9.5-1
	Prescriptive Requirements – Complete if not using Energy Cost Budget Method	
Reference		Standard Compliance
9.5 9.6	9.5 INTERIOR LIGHTING POWER ALLOWANCE BY BUILDING TYPE	
	Calculation of Interior Lighting Power Allowance (ILPA) by Building Type based on Table SB 9.5.1–2017 *	
	Building Type Gross Lighted Area m ²	□ YES □ N/A
	Lighting Power DensityW/m²	
	Total Installed Interior Lighting Power W ≤ value of	
	Interior LPA W *	
	9.6 INTERIOR LIGHTING POWER ALLOWANCE BY SPACE FUNCTION	
	Calculation of Interior Lighting Power Allowance (ILPA) for each space based on Table SB 9.6.1–2017 $\mbox{\ensuremath{^*}}$	□ YES □ N/A
	Total Installed Interior Lighting Power W ≤ value of Interior LPA W *	2.23
	List any exemptions that apply:	

^{*} Calculation worksheet (FORM 9.5-2) is required.

ASHRAE 90.1 & SB-10 - SECTION 9 - LIGHTING COMPLIANCE WORKSHEET

FORM 9.4-3

Project:	Designer Name:

Exterior Building Lighting Power Allowance - refer to Table SB 9.4.2-2–2017				
Location / Application	Allowance	Area or Length (m² or m)	Tradable Power Allowance	
Exterior Lighting Zone		Base Site Allowance		
		Tradable Power Allowance		

Exterior Installed Lighting Power				
ID	Luminaire description (including number of lamps per fixture, watts per	Number of	Watts/	Total
10	lamp, type of ballast, type of fixture)	Luminaires	Luminaire	Watts
	Total Exterior Lighting Power			

^{*} If additional space is required to provide further information, please attach a separate sheet(s) of paper.
** If trade-offs or exceptions are used attach calculations.

ASHRAE 90.1 & SB-10 - SECTION 9 - LIGHTING COMPLIANCE WORKSHEET **FORM 9.5-2** Project: Designer Name: Interior Power Allowance (Building Area Method) -refer to Table SB 9.5.1-2017 Building Lighting Power Density Gross Lighted Floor Area Lighting Power Allowance Allowance (W/m²) (W) (LPDxGLFA) Туре (m²)Total Power Allowance Interior Lighting Power Allowance (Space by Space Method) - refer to Table SB 9.6.1–2017 Lighting Power Density Building Common/Specific Space Area Lighting Power Allowance Space Type Allowance (W/m²) (m²)(W) Type Total Power Allowance

	Interior Connected Lighting Power					
Space ID	Luminaire Description (including number of lamps per fixture, watts per lamp, type of ballast, type of fixture)	Number of Luminaires	Watts/ Luminaire	Total Watts		
,	Total Interior Lighting Power					

^{*} If additional space is required to provide further information, please attach a separate sheet(s) of paper.

^{**} If additional interior lighting power, trade-offs or exceptions are used attach calculations.

SECTION	SECTION 10 OTHER EQUIPMENT - MANDATORY PROVISIONS Form 10.				
Reference	Item	Standard Compliance			
10.4.1	Electric motors are in compliance with Table SB-10 Table 10.4.1.A where applicable; otherwise, they comply with ASHRAE 90.1-2013 Tables 10.8-1, 10.8-2, 10.8-3 and 10.8-6, as applicable.	□ YES			
10.4.2	Service water pressure booster pumps have pressure sensors to vary pump speed and/or start and stop pumps.		□ N/A		
	No devices are installed to reduce the pressure of all of the water supplied by any booster system or pump, except for safety devices.	□ YES	□ N/A		
	Booster pumps shut off when there is no service water flow.	□ YES	□ N/A		
	All elevator cab lighting systems have efficacy of not less than 35 lumens per Watt.	□ YES	□ N/A		
10.4.3	Elevator cab ventilation fans for elevators without air conditioning consume less than 0.7 W·s/L at maximum speed.	□ YES	□ N/A		
	Cab interior light and ventilation is de-energized when elevators are stopped and unoccupied with doors closed for over 15 minutes.	□ YES	□ N/A		
10.4.4	Escalators and moving walks automatically slow to the minimum permitted speed in accordance with ASME A17.1/CSA B44 or applicable local code when not conveying passengers.		□ N/A		
10.4.5	The building is designed to facilitate future installation of means to measure and monitor energy use by each energy type described in Section 10.4.5.1, per SB-10 10.4.5.3.	□ YES	□ N/A		

ASHRAE 90.1-2013 & SB-10 ENERGY COST BUDGET (ECB) COMPLIANCE REPORT

FORM 11

Project: Designer Name:						
Occupancies	Floor Area	Annual Consumption Sum	mary ⁽¹⁾	Reference Building Energy	Proposed Building Energy	Units
□ Assembly		Space Heating				
□ Health/Institutional		Space Cooling				
□ Hotel/Motel		HVAC Fans				
☐ Light Manufacturing _		Pumps				
□ Multifamily						
□ Office		Interior Lighting				
□ Restaurant		Other				
□ Retail _		Other				
□ School						
□ Warehouse		Total Annual Energy				
□ Other				<u>'</u>		
		Total Annual Energy Co	st	\$	> \$	
Total		<i>•</i>	<u> </u>			
_		Total Annual CO2e Emis	ssions		>	
☐ Proposed Building Descript	tion	Peak Electric Demand*			>	
		*OR Building componen				□ YES
		1.1.2.3(5) comply with	the presci	riptive requiremen	ts of ASHRAE 90.1-2013	
		Reference and Proposed Building Energy Consumptions are calculated by:				
		Please specify modelling	software	:		-
		_				(2)
HVAC System Descriptions		į t	nergy Effi	ciency Features in	Proposed Building Design	(2)
Reference Building Design						
						_
						_
						_
						-
		-				
Proposed Building Design		-				
Dutlida a ta ta a 12 12 12						_
Building is in compliance with mandatory requirements of sections			YES			
5.4, 6.4, 7.4, 8.4, 9.4, and 10.4	4.					

Compliance Result

The design detailed in the above referenced plans complies with the mandatory requirements of the ASHRAE 90.1-2013 Standard and the additional requirements of Supplementary Standard SB-10. The calculated proposed building energy cost (design energy cost), CO₂ emissions and peak electric demand do not exceed the calculated reference building energy cost (energy cost budget) CO₂ emissions and peak electric demand. Therefore, this design **DOES COMPLY** with the ASHRAE 90.1-2013 ECB compliance methodology and the additional requirements of Supplementary Standard SB-10.

Individual certifying authenticity of the data provided in this analysis:

Signature:	Name/Title:

Notes: (1) Verify with building official whether full modelling report is required to be submitted

(2) Explain major energy saving features utilized to achieve modelled savings