



ADJACENT SURFACE TO BE FLUSH WITH TOP OF CURB.

30 MPa C.I.P. CONCRETE CURB WITH 2 - 15M BARS CONTINUOUS SAW CUT JOINTS AT 3 650 O.C.

1200 MIN. OFFSET

CONTINUOUS FILTER FABRIC 270R BY TERRAFIX

10 DIA. CLEAR PEA GRAVEL

SLOPE SUBGRADE 2% TO DRAIN TRENCH

ENGINEERED WOOD CHIP SURFACE (SEE SPECIFICATIONS FOR SOURCE)

300 MIN. UNDER PLAY EQUIPMENT

300 MIN.

COMPACT UNDISTURBED SOIL TO 98% SPD. FOR FILL CONDITIONS PLACE 19 mm DIA. CRUSHER RUN LIMESTONE BASE AND COMPACT TO 98% SPD.

COMPACTED SUBGRADE TO 98% SPD
 FILTER FABRIC - TERRAFIX 270R WRAPPED AROUND TRENCH, OVERLAP 150
 100 DIA. PERFORATED P.V.C. DRAIN PIPE WITH FILTER SOCK, SLOPED 2% TO RIGID PIPE CONNECTION
 19 DIA. CLEAR CRUSHED LIMESTONE

100 DIA. RIGID P.V.C. PIPE CONNECTION FROM PLAYGROUND CURB TO C.B. ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS STATED OTHERWISE



PLANNING, DESIGN & DEVELOPMENT DEPARTMENT

TITLE: **PLAY AREA (ENGINEERED WOOD SURFACE) C.I.P. CONCRETE CURB (SECTION)**

DRAWING NO. **PDD 311d**

REVIEWED BY: *SH*

SCALE: N.T.S.

APPROVED BY: *the Walsh*

DATE: JANUARY 2007