



NOTES:

1. BACKSTOP AND FIRST WING EXTENSION TO BE OF ALL WELDED CONSTRUCTION
2. ALL RAILS TO BE "FISH-MOUTH" CUT; CRIMPING WILL NOT BE ACCEPTED
3. CHAIN LINK FABRIC ON BACKSTOP OVERHANG AND VERTICAL SIDES TO BE ONE PIECE SECURED WITH STRETCHER BARS AND BAR BANDS @ 250 O.C.
4. SECURE CHAIN LINK FABRIC TO INTERMEDIATE POSTS AND ALL RAILS WITH 3.5MM GALVANIZED KNUCKLED TIES AT 250 O.C. SECURE CHAIN LINK FABRIC TO BACKSTOP AND WING EXTENSION TERMINAL POSTS USING STRETCHER BARS AND BAR BANDS @ 250 O.C.
5. INSTALL CHAIN LINK FABRIC ON INSIDE (PLAYSIDE) OF BACKSTOP AND ON TOP SIDE OF OVERHANG.
6. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS STATED OTHERWISE.



**PLANNING,
 DESIGN &
 DEVELOPMENT
 DEPARTMENT**

**TITLE:
 JUNIOR SOFTBALL BACKSTOP
 WITH OVERHANG (ELEVATION)**

**DRAWING NO.
 PDD 433**

REVIEWED BY: *SH [Signature]*

SCALE: **N.T.S.**

APPROVED BY: *[Signature]*

DATE: **JANUARY 2007**