



DROPPED CURB AT PEDESTRIAN REFUGE ISLAND AND MID-BLOCK CROSSING WITH TWO STAGE PEDESTRIAN SIGNALS

## **NOTES**

- A. WHEN DISTANCE IS LESS THAN 1.4m USE CONTINUOUS DROPPPED CURB AT INTERSECTION CORNER. WHEN DISTANCE IS GREATER THAN OR EQUAL TO 1.4m USE TWO SEPARATED DROPPED CURBS AT INTERSECTION CORNER.
- DROPPED CURB TO BE PROVIDED FOR WIDTH OF ALL PEDESTRIAN CROSSINGS.
- 2. TACTILE WALKING SURFACE INDICATORS
  TO BE PROVIDED ONLY WITHIN WIDTH OF
  PEDESTRIAN CROSSING.
  TACTILE STRIPS SHALL NOT BE CONTINUOUS
  IF CROSSWALKS ARE SEPARATED.
- 3. TACTILE WALKING SURFACE INDICATORS ARE TO BE INSTALLED AT ALL PEDESTRIAN CROSSINGS IN CONJUNCTION WITH ALL ROAD AND SIDEWALK CONSTRUCTION AND RECONSTRUCTION AND RESURFACING PROJECTS.
- 4. EACH LOCATION IS SITE SPECIFIC AND CONSULTATION WITH THE CITY OF BRAMPTON SHALL BE REQUIRED FOR NON TYPICAL INTERSECTIONS AND PEDESTRIAN CROSSING LOCATIONS.
- 5. REFER TO STD. 284 FOR VARIOUS CONFIGURATIONS OF PEDESTRIAN CROSSINGS AT SIGNALIZED INTERSECTIONS AND STD. 283 FOR CONTROLLED NON SIGNALIZED INTERSECTIONS.

INTERSECTIONS

All dimensions in millimeters unless otherwise shown



APPROVED: JUL 24, 2015

LOCATION OF DROPPED CURBS AT CONTROLLED

**282** 

REV. 1

ORIGINAL: 13/11/2014

N.T.S